



Model KSS with Decision-Maker® MPAC 750 Controller

### Applicable Models

Model	Description
KSS	Standard-Transition Specific Breaker ATS

### Decision-Maker® MPAC 750 Controller Standard Features

- Microprocessor-based controller
- Environmentally sealed user interface
- LED indicators:
  - Contactor position: source N and source E
  - Source available: source N and source E
  - Service required (fault indication)
  - Not in automatic mode
- Test pushbutton. Start and stop loaded or unloaded tests
- Exercise pushbutton. Start and schedule weekly loaded or unloaded exercise.
- Fail-safe transfer for loaded test and exercise functions
- Broadrange voltage sensing (208–600 VAC) on all phases
- Phase-to-phase sensing and monitoring with 0.5% accuracy on both sources
- Frequency sensing with 0.5% accuracy on both sources
- Anti-single phasing protection
- Real-time clock with automatic adjust for daylight saving time and leap year
- Time-stamped event log. View and download event history using Kohler® SiteTech™ software. \*
- Maintenance mode DIP switch
- Isolated RS-485 ports for Modbus connections (9.6, 19.2, and 57.6 kbps)
- Modbus® RTU protocol (Modbus register map available)
- USB port. Connect a personal computer and use Kohler SiteTech software to view events and adjust settings. \*

### Programmable Features

- Program using a personal computer with Kohler® SiteTech® software \*
- Adjustable time delays (see table)
- Overvoltage and undervoltage pickup and dropout settings for the Normal source (see table)
- In-phase monitor (enable/disable and transfer angle)
- Programmable inputs and outputs. Two input and two output connections.

\* SiteTech software is available to Kohler-authorized distributors and dealers.

Modbus is a registered trademark of Schneider Electric.

### Programmable Inputs

- Inhibit transfer
- Remote common fault
- Remote test

### Programmable Outputs

- Auxiliary switch fault
- Auxiliary switch open
- Chicago alarm control
- Common alarm active
- Contactor position
- Exercise active
- Failure to acquire standby source
- Failure to transfer
- Generator engine start, source E
- In-phase monitor sync
- Not in automatic mode
- Phase rotation error
- Test active

Normal Source Voltage Sensing		
Parameter	Default	Adjustment Range
Undervoltage dropout	90% of pickup	75%-98%
Undervoltage pickup	90% of nominal	85%-100%
Overvoltage dropout *	115% of nominal*	106%-135%
Overvoltage pickup	95% of dropout	95%-100%
Voltage dropout time	0.5 sec.	0.1-9.9 sec.

\* 690 volts, maximum. Default = 110% for 600 volt applications.

Adjustable Time Delays		
Time Delay	Default	Adjustment Range
Engine start	3 sec.	0-6 sec.
Engine cooldown	5 min.	0-60 min.
Fail to acquire standby source	1 min.	
Transfer, preferred to standby	3 sec.	
Transfer, standby to preferred	15 min.	

**Note:** Time delays are adjustable in 1 second increments, except as noted.

Environmental Specifications	
Operating Temperature	-20°C to 70°C (-4°F to 158°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Humidity	5% to 95% noncondensing

Main Board I/O Specifications	
Output contact type	Isolated form C (SPDT)
Output contact rating	1 amp @ 30 VDC, 500 mA @120 VAC
I/O terminals wire size	#12-24 AWG

## Controller Accessories

Accessories are available either factory-installed or as loose kits, unless otherwise noted.

### Controller Disconnect Switch

- Disconnects power to controller without disconnecting load
- Mounts inside the enclosure

### Ethernet Communications

- RJ-45 connector
- Supports Internet Protocol version 4 (IPv4)
- Supports Modbus TCP/IP Protocol

### Padlockable User Interface Cover

- Cover is standard on NEMA 3R enclosures

### Programmable Exercise Timer

- Seven-day programmable timer allows scheduling up to 56 on/off events
- LCD display indicates day, time, program/run modes, and on/off/skip status
- Skip next cycle button
- 5-year lithium backup battery

### RSA III Remote Serial Annunciator

- Monitors the generator set
- Monitors ATS common alarm, Normal source, and Emergency source status and connection
- Allows remote testing of the ATS
- For more information about RSA III features and functions, see specification sheet G6-139

**DISTRIBUTED BY:**

Availability is subject to change without notice. Kohler Co. reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever. Contact your local Kohler® Power Systems distributor for availability.